

MULTI-PURPOSE METALLIC PRIMER



Description: Universal primer suitable for above and below the waterline on all substrates with good waterproofing and corrosion resisting performance. Also suitable as a primer or barrier coat under PREMIER and other traditional antifoulings. Contains leafing pigment (excellent sealing/binding properties). Easy to apply and relatively quick drying.

Area of use:

Boat hulls, topsides and superstructure.

Substrates:

GRP, wood, steel and ferro cement.

Packing:

1 litre and 2.5 litre

Physical Constants:

Colour: Grey

Finish: Matt

Volume solids: 60%

Theoretical spreading rate: 12sq.metres per litre

Flash point: 42°C

Specific gravity: 1.17

Dry to touch: 2 hours

Overcoating time: 6 hours

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method: Brush Conventional spray Airless spray Roller

Thinner: PREMIER Antifouling Thinners

Cleaning of tools: PREMIER Antifouling Thinners

Surface condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

Please refer to the Material Safety Data Sheet for further information.